

混合式步行星齿轮减速电机 (内齿圈材质: 金属)

Planetary Gear Stepping Motor (Ring Gear Material: Metal)

52JXM200K/42STH $\Phi 52$ 行星减速器, 允许转矩范围: 6N.m~20N.m
52mm OD Gearbox,
Permissible Load Range: 6N.m~20N.m

行星齿轮减速器 Planetary Gearbox

内齿圈材料	Ring material	金属 Metal
输出轴轴承形式	Bearing at output	滚动轴承 Ball bearings
最大允许径向负载 (离法兰10mm处) Max. Radial load(10mm from flange)		$\leq 80\text{N}$
最大允许轴向负载 Max. shaft axial load		$\leq 30\text{N}$
径向间隙 (测量点尽量接近法兰) Radial play of shaft (near to flange)		$\leq 0.06\text{ mm}$
轴向间隙 Axial play of shaft		$\leq 0.3\text{ mm}$
背隙 (无负载时) Backlash at no-load		$\leq 1.5^\circ$



42STH 混合式步进电机性能 42STH Hybrid Stepping Motor Specifications

Model No.	额定电压 Rated Voltage	每相电流 Current /Phase	每相电阻 Resistance /Phase	每相电感 Inductance /Phase	保持转矩 Holding Torque	引出线数 # of Leads	转动惯量 Rotor Inertia	重量 Weight	长度 L1 Length L1	适配减速比 Max. Gear Ratio
单轴 Single Shaft	V	A	Ω	mH	kg.cm		g-m ²	kg	mm	
42STH38-1206A	4	1.2	3.3	3.2	2.6	6	54	0.28	40	$\leq 1:316$
42STH38-0806A	6	0.8	7.5	6.7	2.6	6				$\leq 1:316$
42STH38-0406A	12	0.4	30	30	2.6	6				$\leq 1:316$
42STH38-1684A	2.8	1.68	1.65	3.2	3.6	4				$\leq 1:247$
42STH47-1206A	4	1.2	3.3	2.8	3.17	6	68	0.35	48	$\leq 1:247$
42STH47-0806A	6	0.8	7.5	6.3	3.17	6				$\leq 1:247$
42STH47-0406A	12	0.4	30	25	3.17	6				$\leq 1:247$
42STH47-1684A	2.8	1.68	1.65	2.8	4.4	4				$\leq 1:106$

常规产品是单出轴, 可以订货双出轴, 型号的后缀号A改为B。 A Single Shaft, B Double shaft

52JXM200K行星减速器性能 52JXM200K Planetary Gearbox Specifications

减 速 比 Reduction ratio	4.5	6.25	8	20	28	34	50	64	91	127	162
减速级数 Number of gear trains	1			2							3
减速器长度 (L2) Length(L2) mm	49			65							80
最大额定转矩 Max. rated torque kg.cm	6			25							50
瞬间允许转矩 Short time permissible torque kg.cm	18			75							150
效 率 Efficiency %	90%			81%							73%

外形和安装尺寸 Dimensions

